

BB0030

BlackBox™
Rack Mount Case



BB0030 BlackBox™ 3U Rack Mount Case

Part #BB0030-0000-110

These lightweight, compact, and double ended cases offer light to medium duty protection and boast significantly better light duty shock performance than the competition. The use of recycled materials in the shell and a sturdy steel frame offer great value while upholding Hardigg's industry-leading standards. When you need to be cost-conscious but can't sacrifice performance, BlackBox is the answer.

- 24" (61 cm) Rugged steel rack frame with 10-32 threads designed to meet ANSI/EIA 310-C
- Rack designed for applications up to 100 lbs (45 kg)
- Shock mounts provide 2" (5.1cm) of sway space to isolate equipment
- 2" (5.1cm) lid and 5" (12.7cm) lid with edge casters



- Engineered racks provide a secure and mobile electronics enclosure
- 2 wheels
- Lightweight and compact
- Shock-mounts
- Shock mounts provide 5.1cm of sway space to isolate equipment
- Molded-in rib design provides secure stacking and interlock
- Patented wide-design Comfort grip handles™ make lifting easy
- Black hardware is long-lasting and fastens securely
- APPLICATION EXAMPLES:
- Audio/Video recording and processing systems
- Satellite communication systems
- Radio communication systems
- Seismic data recording instrumentation
- Climate data collection

BB0030 BlackBox™ 3U Rack Mount Case Configurations

Cat. #	Description
BB0030	BB0030 BlackBox™ 3U Rack Mount Case



Black

BB0030 BlackBox™ 3U Rack Mount Case Specifications

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
38.50" x 24.60" x 11.40" (97.8 x 62.5 x 28.9 cm)			
Rack Length	Rack Width	Rack Height U-Size	
24.00" (60.9 cm)	19.00" (48.2 cm)	5.25" (13.3 cm)	
Lid Interior Dimension (Front)		Lid Interior Dimension (Back)	
2.2" (5.6 cm)		5.2" (13.2 cm)	
Weight		Buoyancy Max.	

42 lbs. (19.05 kg)

348.09 lbs.
(157.89 kg)

Range Temperature

No. of Wheels

2

All dimensions are approximate